TECHNICAL DATA SHEET

REV: 01 DATE: 31 JUL 2018

LARSSÖN[®]

SUPER GLUE



DESCRIPTION:

Larssön SUPER GLUE is fast, practical and very powerful. Easy to apply in almost every surface: bonds metal, wood, rubbers, plastic, leather, ceramics, glass and fabric.

FEATURES:

- ♦ EASY TO APPLY.
- ◆ FAST SETTING WITHIN SECONDS.
- ♦ STRONG BONDING STRENGTH, ESPECIALLY ON SMOOTH SURFACE WITHOUT GAP.
- COST SAVING.

USES:

Easy to apply in almost every surface: bonds metal, wood, rubbers, plastic, leather, ceramics, glass and fabric.

WE RECOMMEND PRELIMINARY COMPATIBILTY TESTS
PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS

NOT RECOMMENDED FOR:

Do not use in areas of constant water immersion. Not for: PE, PP, PTFE and Bituminous surface.

APPLICATION:

- •Surface must be clean, dry and free from grease and old glue
- Apply to one surface only
- Apply suitable pressure on bonding substrates /
- •Clean off excess adhesive with acetone

CURING TIME:

Adhesive will bond in approximately 30 - 45 seconds under room temperature.

SPECIFICATION:

APPEARANCE ODOUR CLEAR SPECIFIC GRAVITY PUNGE VISCOSITY 1.05 ±

CLEAR LIQUID.
PUNGENT SMELL.
1.05 ± 0.05

100 CPS APPROX.

APPLICATION TEMP. -10°C TO 40°C SERVICE -10°C TO 60°C

TEMPERATURE SHELF LIFE

F LIFE 6 MONTHS @ 20°C

STORAGE:

Material should be stored in a dry and cool place, below +20 °C.

CAUTION:

- •Bonds skin and eyes in seconds / Pega la piel y los ojos en pocos segundos.
- •Serious eye damage or eye irritation when in contact
- •In case of skin or eye contact, wash with plenty of water
- •Use only outdoors or in a well-ventilated area
- •Wear protective gloves, clothing, eyes and face protection

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.